

Flat Lift

The FLAT LIFT technology has attained, in the 4 current lift versions, goals never achieved before as far as the minimum height – capacity ratio is concerned.



MODELS OF THE LINE		FI.TIM FLAT				PATENTED			
	Lorem Ipsum	GF 39	KW 50	NM 65	MT 75				
	mm / inch	39 mm / 1.53"	50 mm / 1.97"	65 mm / 2.56"	75 mm / 2.95"				
	Kg / Lb	900 Kg / 1984 Lb	1500 Kg / 3306 Lb	3000 Kg / 6613 Lb	3000 Kg / 6613 Lb				
	mm / inch	1180 mm / 46.45"	1180 mm / 46.45"	1210 mm / 47,63"	1530 mm / 60.23"				
		MOTORSPORT	MOTORSPORT CLASSIC CAR	BODY SHOP / WORKSHOP / TIRE SHOP					



MAXIMUM CAPACITY FROM THE FULLY LOWERED POSITION
In accordance with the EN 1493 VEHICLE LIFTS European standard
Lowering stop device and acoustic signal



Mechanical and hydraulic safety devices


Load testing +50%



FLAT LIFT

GF 39

mm 39 mm
Kg 900 kg
mm 1180 mm



MOTORSPORT



MAXIMUM CAPACITY FROM THE FULLY LOWERED POSITION

NM 65

mm 65 mm
Kg 3000 kg
mm 1210 mm



BODY SHOP
WORKSHOP
TIRE SHOP



Holes in the 4 corners for lifting and / or anchoring accessories

